



# **Cúram 8.2.2**

## **Intake Developer's Guide**



## Note

---

Before using this information and the product it supports, read the information in [Notices on page 37](#)



# Edition

---

This edition applies to Cúram 8.2.2.

© Merative US L.P. 2012, 2026

Merative and the Merative Logo are trademarks of Merative US L.P. in the United States and other countries.



# Contents

---

<b>Note.....</b>	<b>iii</b>
<b>Edition.....</b>	<b>v</b>
<b>1 Developing with Intake.....</b>	<b>9</b>
1.1 Introduction.....	9
Overview.....	9
Purpose.....	9
Audience.....	9
1.2 Defining triage.....	9
Introduction.....	11
Setting up a Triage Definition.....	11
Adding Urgent Alerts to the Rule Set.....	12
Recommending Services.....	12
Recommending Programs.....	12
1.3 Defining screenings.....	13
Introduction.....	13
Setting up a Screening Definition.....	13
Adding urgent alerts to the rule set.....	27
Recommending programs.....	27
1.4 Configuring Check Eligibility.....	28
Introduction.....	28
Configuring an Application Case for Eligibility Checks.....	29
Configuring the Eligibility Check Rule Set.....	29
Configuring the Results Display Page.....	30
1.5 Configuring a PCR Rule Set.....	30
Introduction.....	30
Configuring a PCR Rule Set.....	30
Mandatory Rule Attributes.....	31
Specifying Rule Set Properties Text.....	32
1.6 Configuring Authorization Rule Sets.....	32
Introduction.....	32
Intake Rule Sets.....	32
Determining the Programs to be Authorized.....	33
Writing the Authorize Application Rule Class.....	33
Determining the Clients to be Added to the Product Delivery.....	33
Writing the Client Selection Rule Class.....	34
1.7 Intake Process XML Definition.....	34
Intake Process XML Definition.....	34

1.8 Intake Environment Variables..... 34

Application Properties..... 34

**Notices..... 37**

Privacy policy..... 38

Trademarks..... 38

# 1 Developing with Intake

---

An intake process definition XML document is required for Intake. Triage and screening definitions are configured in the intake process definition XML document. There are three configuration options for the application case that drive the check eligibility process: eligibility check rule set, eligibility check strategy, and the results page. A PCR rule set is required for PCR processing. Application authorization rules sets must also be configured.

## 1.1 Introduction

---

### Overview

Use this information to understand the functions that Cúram Intake supports for collecting data when a client applies to an organization for benefits or services provided by that organization.

Cúram Intake provides functions to support the following intake processes:

- Application
- Triage
- Screening

Each of these processes can be used for capturing data about the client when they apply to an organization for benefits or services provided by that organization. Defining triage and screening, and the configurations that are required for each, is covered in the following documentation.

Configuring an application is covered in the *Cúram Intake Configuration Guide*.

### Purpose

This document provides an overview of the Cúram Intake development process. It details key elements such as the configurations required for screening and triage as well as the rule sets which need to be configured for running PCR, checking eligibility, selecting clients, and authorizing at the application case level.

### Audience

This guide is intended to be used by architects and developers interested in configuring a custom Intake solution.

## 1.2 Defining triage

---

Triage allows a caseworker to quickly gauge a client's needs by asking a core set of fundamental questions. The result allows the caseworker to understand the client's situation in relation to the

core needs. A triage can be performed by the caseworker resulting in a list of suitable services, service providers, and programs to help meet the client's needs.

### Setting up a triage definition

Set up a triage definition as follows:

- Open the XML document that represents the intake process definition - see Appendix A.
- Create or locate an XML element `IndividualConfiguration` as a direct child of the `IntakeProcess` element.

**Note:** Only one `IndividualConfiguration` element can exist in the document.

- Create or locate an XML element `Triage` as a direct child of the `IndividualConfiguration` element previously located.
- Specify the following attributes on this element to define the Triage process:

Table 1: Triage Attributes

Attribute Name	Type	Purpose
<i>DataStore</i>	String	Specifies the name of the datastore schema to be used for the IEG script that is run to capture the details of the triage.
<i>RuleSet</i>	String	Specifies the name of the CER rule set to be used to process the answers from the script into recommendations for programs and services.
<i>RuleSetClass</i>	String	Specifies the name of the CER rule class in the CER rule set that is used to calculate the recommendations of the triage.
<i>ScriptName</i>	String	Specifies the name of the IEG script that is run to capture the details of the triage.
<i>ScriptType</i>	String	Specifies the type of IEG script that is run to capture the details of the triage.
<i>ScriptVersion</i>	String	Specifies the type of IEG script that is run to capture the details of the triage.

### Adding urgent alerts to the rule set

To output an urgent alert from the CER rule set, the rule class that is defined in the triage definition should have an attribute that is named `alertMessages`. This attribute has as its type a list of rule classes of type `AlertMessage`. Each `AlertMessage` that is calculated and passed into this list appears as an urgent alert on the **Triage Result** page.

### Recommending services

To recommend a service from the CER rule set, the rule class that is specified in the triage definition should have an attribute that is named `services`. This attribute has as its type a list of rule classes that subclass the `AbstractService` type. Each `AbstractService` that is calculated and passed into this list appears as a recommended service on the **Triage Result** page.

## Recommending programs

To recommend a program from the CER rule set, the rule class that is defined as part of triage definition should have an attribute that is named `programs`. This attribute has as its type a list of rule classes that subclass the type `AbstractProgram`. Each `AbstractProgram` that is calculated and passed into this list appears as a recommended program on the **Triage Result** page.

## Introduction

Triage allows a case worker to quickly gauge a client's needs when they phone or visit by asking a core set of fundamental questions. The result allows the case worker to understand the client's situation in relation to the core needs. A triage can be performed by the case worker resulting in a list of suitable services, service providers, and programs to help meet the client's needs.

## Setting up a Triage Definition

- Open the XML document which represents the intake process definition - see Appendix A.
- Create or locate an XML element `IndividualConfiguration` as a direct child of the `IntakeProcess` element.

**Note:** Only one `IndividualConfiguration` element may exist in the document.

- Create or locate an XML element `Triage` as a direct child of the `IndividualConfiguration` element previously located.
- On this element the following attributes can be specified which will define the Triage process:

*Table 2: Triage Attributes*

This table describes the attributes for a triage definition:

Attribute Name	Type	Purpose
<code>DataStore</code>	String	This attribute specifies the name of the datastore schema to be used for the IEG script that will be executed to capture the details of the triage.
<code>RuleSet</code>	String	This attribute specifies the name of the CER rule set to be used to process the answers from the script into recommendations for programs and services.
<code>RuleSetClass</code>	String	This attribute specifies the name of the CER rule class in the CER rule set which is used to calculate the recommendations of the triage.

Attribute Name	Type	Purpose
ScriptName	String	This attribute specifies the name of the IEG script which will be used to capture the details of the triage.
ScriptType	String	This attribute specifies the type of IEG script which will be used to capture the details of the triage.
ScriptVersion	String	This attribute specifies the type of IEG script which will be used to capture the details of the triage.

## Adding Urgent Alerts to the Rule Set

To output an urgent alert from the CER rule set, the rule class defined in the triage definition should have an attribute named `alertMessages`. This attribute has as its type a list of rule classes of type `AlertMessage`. Each `AlertMessage` which is calculated and passed into this list will appear as an urgent alert on the Triage Result page in the application.

## Recommending Services

To recommend a service from the CER rule set, the rule class specified in the triage definition should have an attribute named `services`. This attribute has as its type a list of rule classes which subclass the `AbstractService` type. Each `AbstractService` which is calculated and passed into this list will appear as a recommended service on the Triage Result page in the application.

## Recommending Programs

To recommend a program from the CER rule set, the rule class defined as part of triage definition should have an attribute named `programs`. This attribute has as its type a list of rule classes which subclass the type `AbstractProgram`. Each `AbstractProgram` which is calculated and passed into this list will appear as a recommended program on the Triage Result page in the application.

## 1.3 Defining screenings

Screening allows a client to determine whether they are potentially eligible for one or more programs based on a set of high level, guided questions. Potential eligibility for the selected programs is determined by running eligibility rules against the client's responses to the questions.

### Introduction

Screening allows a client to determine if they are potentially eligible for one or more programs based on a set of high level, guided questions. Potential eligibility for the selected programs is determined by running eligibility rules against the client's responses to the questions.

### Setting up a Screening Definition

- Open the XML document which represents the intake process definition - see Appendix A.
- Create or locate an XML element `IndividualConfiguration` as a direct child of the `IntakeProcess` element. Only one `IndividualConfiguration` element may exist in the document.
- Create or locate an XML element `Screening` as a direct child of the `IndividualConfiguration` element previously located. There can be as many `Screening` elements as are required.
- On this element the following attributes can be specified which are used to define the screening process.

Table 3: Screening Attributes

This table describes the attributes that can be set for a screening definition.

Attribute Name	Type	Purpose
Type	Code Table Entry	This attribute specifies the category of screening. The category is an entry from the ScreeningCategory code table. Only one screening script can be specified for each screening category, and as such this is a unique attribute.
DataStore	String	This attribute specifies the name of the data store schema to be used for the IEG script that is executed to capture the details of the screening.
RuleSet	String	This attribute specifies the name of the CER rule set to be used to process the answers from the screening script into recommendations for programs.

Attribute Name	Type	Purpose
RuleSetClass	String	This attribute specifies the name of the CER rule class in the CER rule set which is used to calculate the recommendations of the screening.
ScriptName	String	This attribute specifies the name of the IEG script which is used to capture the details of the triage.
ScriptVersion	String	This attribute specifies the type of IEG script which will be used to capture the details of the triage.

### Specifying whether Programs are Available Internally or Externally

- Open the XML document which represents the intake process definition - see Appendix A.
- Locate the XML element Screening which is to be defined.
- For each program that the intake process will support, create an element ProgramType as a direct child of the Screening element.
- For each program that the intake process will support, create an element ProgramType as a direct child of the Screening element.

Table 4: ProgramType Attributes for a Screening

This table describes the attributes that can be set for a screening definition.

Attribute Name	Type	Purpose
ProgramType	Code Table Entry	This attribute should contain an entry from the code table 'ProgramType'. This is a code table which specifies a program type, e.g. medical assistance. This attribute is mandatory and must be specified.
Availability	String	This attribute should contain the value 'internal' if the program is available internally or 'external' if the program is available from a different agency.

- **DisplayStatus: SCREENINGSTATUS:** The set of statuses for which a screening should be displayed on the list pages. If a status is not listed here then screenings of that status will not be displayed in the user interface.

```
<?xml version="1.0" encoding="UTF-8"?>
  <codetables package="curam.intake.codetable">
    <codetable java_identifier="SCREENINGSTATUS"
      name="SCREENINGSTATUS">
      <displaynames>
        <locale language="en">Screening Status</locale>
      </displaynames>
    </codetable>
  </codetables>
```

```

<code default="true" java_identifier="IN_PROGRESS"
  status="ENABLED" value="SS19001">
<locale language="en" country="US" sort_order="0">
<description>In-Progress</description>
<annotation></annotation>
</locale>
</code>
<code default="false" java_identifier="COMPLETE"
  status="ENABLED" value="SS19002">
<locale language="en" country="US" sort_order="0">
<description>Complete</description>
<annotation></annotation>
</locale>
</code>
<code default="false" java_identifier="CANCELLED"
  status="ENABLED" value="SS19003">
<locale language="en" country="US" sort_order="0">
<description>Cancelled</description>
<comments>Comments for Rejected in EN_US</comments>
<annotation></annotation>
</locale>
</code>
</codetable>
</codetables>

```

Figure 1: For example:

Following are the codes in CT\_ScreeningStatus.ctx:

- Now, Please refer to the following example for guidance:

```

<Screening DataStore="InternalApplication"
RuleSet="FinancialAssistanceRuleSet"
RuleSetClass="FinancialAssistance"
  ScriptName="FinancialAssistanceApplicationScreening"
  ScriptVersion="V1" type="SC19001" >
  <ProgramType availability="internal" type="PT19001"/>
  <ProgramType availability="internal" type="PT19002"/>
  <ProgramType availability="internal" type="PT19003"/>
  <DisplayStatus status="SS19002"/>
  <DisplayStatus status="SS19001"/>
</Screening>

```

1.) Create the file CommonIntakeProcess.xml in the <EJBSERVER\_HOME>\components\CommonIntake\data\initial\clob" folder.

2.)Following entries need to be made in the DMX files:

Note: If the dmx does not exist, then need to create a dmx file.

```

<row>
  <attribute name="intakeProcessID">
    <value>27900</value>
  </attribute>
  <attribute name="name">
    <value>CommonIntakeProcess</value>
  </attribute>
  <attribute name="state">
    <value>IPDS19002</value>
  </attribute>

```

```

<attribute name="version">
<value>1</value>
</attribute>
</row>

```

2.1) INTAKEPROCESSNAME.dmx - Entry of the Screening Process Name.

2.2) INTAKEPROCESSCONFIGURATION.dmx - Entry of the process configuration.

```

<row>
  <attribute name="intakeProcessConfigurationID">
    <value>27900</value>
  </attribute>
  <attribute name="intakeProcessNameID">
    <value>27900</value>
  </attribute>
  <attribute name="optionXML">
    <value>./CommonIntake/data/initial/clob/
CommonIntakeProcess.xml</value>
  </attribute>
</row>

```

2.3) INTAKEPROCESSROLEASSIGNMENT.dmx - Entry of the process role assignment.

```

<row>
  <attribute name="intakeProcessRoleAssignmentID">
    <value>27900</value>
  </attribute>
  <attribute name="intakeProcessID">
    <value>27900</value>
  </attribute>
  <attribute name="role">
    <value>CIAPP</value>
  </attribute>
  <attribute name="recordStatus">
    <value>RST1</value>
  </attribute>
</row>

```

2.4) IEGSCRIPTINFO.dmx - Information about where the IEG script is residing.

```

<row>
  <attribute name="scriptID">
    <value>FinancialAssistanceApplicationScreening</value>
  </attribute>
  <attribute name="type">
    <value>Screening</value>
  </attribute>
  <attribute name="scriptVersion">
    <value>V1</value>
  </attribute>
  <attribute name="name">
    <value>FinancialAssistanceApplicationScreening</value>
  </attribute>
  <attribute name="scriptDefinition">

```

```

    <value>./CommonIntake/data/initial/clob/
FinancialAssistanceApplicationScreening_V1_Screening.xml</
value>
  </attribute>
  <attribute name="status">
    <value>ISS02</value>
  </attribute>
  <attribute name="versionNo">
    <value>1</value>
  </attribute>
  <attribute name="lastWritten">
    <value>SYSTIME</value>
  </attribute>
</row>

```

Note: If the dmx does not exist, then need to create a dmx file.

```

<row>
  <attribute name="creoleRuleSetID">
    <value>27011</value>
  </attribute>
  <attribute name="name">
    <value>FinancialAssistanceRuleSet</value>
  </attribute>
  <attribute name="ruleSetDefinition">
    <value>../../build/svr/creole.gen/Rules/components/
CommonIntake/FinancialAssistanceRuleSet.xml</value>
  </attribute>
  <attribute name="ruleSetVersion">
    <value/>
  </attribute>
  <attribute name="versionNo">
    <value>1</value>
  </attribute>
</row>

```

2.5)CREOLERULESET.dmx - Rule set information which is used to determine which products is the user eligible.

```

<row>
  <attribute name="schemaName">
    <value>InternalApplication</value>
  </attribute>
  <attribute name="schemaText">
    <value>./CommonIntake/data/initial/clob/
InternalApplication.xsd</value>
  </attribute>
  <attribute name="versionNo">
    <value>1</value>
  </attribute>
  <attribute name="lastWritten">
    <value>SYSTIME</value>
  </attribute>
</row>
<row>
  <attribute name="schemaName">
    <value>InternalApplicationDomains</value>
  </attribute>
  <attribute name="schemaText">

```

```

    <value>./CommonIntake/data/initial/clob/
InternalApplicationDomains.xsd</value>
  </attribute>
  <attribute name="versionNo">
    <value>1</value>
  </attribute>
  <attribute name="lastWritten">
    <value>SYSTIME</value>
  </attribute>
</row>

```

## 2.6) DATASTORESCHEMA.dmx - Datastore information which is used by the IEG script.

```

<row>
  <attribute name="schemaName">
    <value>InternalApplication</value>
  </attribute>
  <attribute name="type">
    <value>DSST1</value>
  </attribute>
  <attribute name="localeIdentifier">
    <value language="en">en</value>
  </attribute>
  <attribute name="localizedText">
    <value language="en">The Internal Applications Schema</
value>
  </attribute>
  <attribute name="versionNo">
    <value>1</value>
  </attribute>
  <attribute name="lastWritten">
    <value>SYSTIME</value>
  </attribute>
</row>
<row>
  <attribute name="schemaName">
    <value>InternalApplicationDomains</value>
  </attribute>
  <attribute name="type">
    <value>DSST1</value>
  </attribute>
  <attribute name="localeIdentifier">
    <value language="en">en</value>
  </attribute>
  <attribute name="localizedText">
    <value language="en">The Internal Applications Domains
Schema</value>
  </attribute>
  <attribute name="versionNo">
    <value>1</value>
  </attribute>
  <attribute name="lastWritten">
    <value>SYSTIME</value>
  </attribute>
</row>

```

## 2.7) DATASTORESCHEMATRANSLATION.dmx - Data store schema translation information

```

<row>
  <attribute name="resourceid">
    <value>19431</value>
  </attribute>
  <attribute name="localeIdentifier">
    <value/>
  </attribute>
  <attribute name="name">
    <value>financialassistance_about_you.png</value>
  </attribute>
  <attribute name="contentType">
    <value>image/png</value>
  </attribute>
  <attribute name="contentDisposition">
    <value>inline</value>
  </attribute>
  <attribute name="content">
    <value>./CommonIntake/data/initial/blob/
financialassistance_about_you.png</value>
  </attribute>
  <attribute name="internal">
    <value>0</value>
  </attribute>
  <attribute name="lastWritten">
    <value>SYSTIME</value>
  </attribute>
  <attribute name="versionNo">
    <value>1</value>
  </attribute>
  <attribute name="category">
    <value>RS_IMG</value>
  </attribute>
</row>
<row>
  <attribute name="resourceid">
    <value>19432</value>
  </attribute>
  <attribute name="localeIdentifier">
    <value/>
  </attribute>
  <attribute name="name">
    <value>financialassistance_title_about_you.png</value>
  </attribute>
  <attribute name="contentType">
    <value>image/png</value>
  </attribute>
  <attribute name="contentDisposition">
    <value>inline</value>
  </attribute>
  <attribute name="content">
    <value>./CommonIntake/data/initial/blob/
financialassistance_title_about_you.png</value>
  </attribute>
  <attribute name="internal">

```

```

    <value>0</value>
  </attribute>
  <attribute name="lastWritten">
    <value>SYSTIME</value>
  </attribute>
  <attribute name="versionNo">
    <value>1</value>
  </attribute>
  <attribute name="category">
    <value>RS_IMG</value>
  </attribute>
</row>
<row>
  <attribute name="resourceid">
    <value>19433</value>
  </attribute>
  <attribute name="localeIdentifier">
    <value/>
  </attribute>
  <attribute name="name">
    <value>Application Form.pdf</value>
  </attribute>
  <attribute name="contentType">
    <value>image/png</value>
  </attribute>
  <attribute name="contentDisposition">
    <value>inline</value>
  </attribute>
  <attribute name="content">
    <value>./CommonIntake/data/initial/blob/Application
Form.pdf</value>
  </attribute>
  <attribute name="internal">
    <value>0</value>
  </attribute>
  <attribute name="lastWritten">
    <value>SYSTIME</value>
  </attribute>
  <attribute name="versionNo">
    <value>1</value>
  </attribute>
  <attribute name="category">
    <value/>
  </attribute>
</row>
<row>
  <attribute name="resourceID">
    <value>19434</value>
  </attribute>
  <attribute name="localeIdentifier">
    <value/>
  </attribute>
  <attribute name="name">
    <value>FinancialAssistanceApplication_V1_Intake</value>
  </attribute>
  <attribute name="contentType">
    <value>text/plain</value>
  </attribute>

```

```

        <attribute name="contentDisposition">
        <value>inline</value>
        </attribute>
        <attribute name="content">
        <value>./CommonIntake/data/initial/blob/
financialAssApplication.properties</value>
        </attribute>
        <attribute name="internal">
        <value>0</value>
        </attribute>
        <attribute name="lastWritten">
        <value>SYSTIME</value>
        </attribute>
        <attribute name="versionNo">
        <value>1</value>
        </attribute>
        <attribute name="category">
        <value>RS_PROP</value>
        </attribute>
    </row>
    <row>
        <attribute name="resourceid">
        <value>19435</value>
        </attribute>
        <attribute name="localeIdentifier">
        <value/>
        </attribute>
        <attribute name="name">
        <value>financial-ass-app-config</value>
        </attribute>
        <attribute name="contentType">
        <value>text/plain</value>
        </attribute>
        <attribute name="contentDisposition">
        <value>inline</value>
        </attribute>
        <attribute name="content">
        <value>./CommonIntake/data/initial/blob/financial-ass-app-
config.properties</value>
        </attribute>
        <attribute name="internal">
        <value>0</value>
        </attribute>
        <attribute name="lastWritten">
        <value>SYSTIME</value>
        </attribute>
        <attribute name="versionNo">
        <value>1</value>
        </attribute>
        <attribute name="category">
        <value>RS_PROP</value>
        </attribute>
    </row>
    <row>
        <attribute name="resourceID">
        <value>19436</value>
        </attribute>
        <attribute name="localeIdentifier">

```

```

    <value/>
  </attribute>
  <attribute name="name">

    <value>FinancialAssistanceApplication_V1_Intake_AboutTheClaimantContinu
value>
    </attribute>
    <attribute name="contentType">
    <value>text/plain</value>
    </attribute>
    <attribute name="contentDisposition">
    <value>inline</value>
    </attribute>
    <attribute name="content">
    <value>./CommonIntake/data/initial/blob/
AboutTheClaimantContinue.properties</value>
    </attribute>
    <attribute name="internal">
    <value>0</value>
    </attribute>
    <attribute name="lastWritten">
    <value>SYSTIME</value>
    </attribute>
    <attribute name="versionNo">
    <value>1</value>
    </attribute>
    <attribute name="category">
    <value>RS_PROP</value>
    </attribute>
  </row>
  <row>
    <attribute name="resourceID">
    <value>19437</value>
    </attribute>
    <attribute name="localeIdentifier">
    <value/>
    </attribute>
    <attribute name="name">

    <value>FinancialAssistanceApplicationScreening_V1_Screening_AboutTheCla
value>
    </attribute>
    <attribute name="contentType">
    <value>text/plain</value>
    </attribute>
    <attribute name="contentDisposition">
    <value>inline</value>
    </attribute>
    <attribute name="content">
    <value>./CommonIntake/data/initial/blob/
AboutTheClaimantContinue.properties</value>
    </attribute>
    <attribute name="internal">
    <value>0</value>
    </attribute>
    <attribute name="lastWritten">
    <value>SYSTIME</value>
    </attribute>

```

```

        <attribute name="versionNo">
        <value>1</value>
        </attribute>
        <attribute name="category">
        <value>RS_PROP</value>
        </attribute>
    </row>
    <row>
        <attribute name="resourceID">
        <value>19439</value>
        </attribute>
        <attribute name="localeIdentifier">
        <value/>
        </attribute>
        <attribute name="name">

    <value>FinancialAssistanceApplicationScreening_V1_Screening</
value>
        </attribute>
        <attribute name="contentType">
        <value>text/plain</value>
        </attribute>
        <attribute name="contentDisposition">
        <value>inline</value>
        </attribute>
        <attribute name="content">
        <value>./CommonIntake/data/initial/blob/
financialAssApplicationScreening.properties</value>
        </attribute>
        <attribute name="internal">
        <value>0</value>
        </attribute>
        <attribute name="lastWritten">
        <value>SYSTIME</value>
        </attribute>
        <attribute name="versionNo">
        <value>1</value>
        </attribute>
        <attribute name="category">
        <value>RS_PROP</value>
        </attribute>
    </row>
    <row>
        <attribute name="resourceID">
        <value>19440</value>
        </attribute>
        <attribute name="localeIdentifier">
        <value/>
        </attribute>
        <attribute name="name">

    <value>curam.humanservicesscreening.rules.FinancialAssistanceInternalSc
value>
        </attribute>
        <attribute name="contentType">
        <value>text/plain</value>
        </attribute>
        <attribute name="contentDisposition">

```

```

        <value>inline</value>
      </attribute>
      <attribute name="content">
        <value>./CommonIntake/data/initial/blob/
FinancialAssistanceInternalScreening.properties</value>
      </attribute>
      <attribute name="internal">
        <value>0</value>
      </attribute>
      <attribute name="lastWritten">
        <value>SYSTIME</value>
      </attribute>
      <attribute name="versionNo">
        <value>1</value>
      </attribute>
      <attribute name="category">
        <value>RS_PROP</value>
      </attribute>
    </row>
    <row>
      <attribute name="resourceID">
        <value>19441</value>
      </attribute>
      <attribute name="localeIdentifier">
        <value/>
      </attribute>
      <attribute name="name">
        <value>CIIntakeProcess.GlobalConfiguration</value>
      </attribute>
      <attribute name="contentType">
        <value>text/plain</value>
      </attribute>
      <attribute name="contentDisposition">
        <value>inline</value>
      </attribute>
      <attribute name="content">
        <value>./CommonIntake/data/initial/blob/
CIIntakeProcessGlobalConfiguration.properties</value>
      </attribute>
      <attribute name="internal">
        <value>0</value>
      </attribute>
      <attribute name="lastWritten">
        <value>SYSTIME</value>
      </attribute>
      <attribute name="versionNo">
        <value>1</value>
      </attribute>
      <attribute name="category">
        <value>RS_PROP</value>
      </attribute>
    </row>
    <row>
      <attribute name="resourceID">
        <value>1942</value>
      </attribute>
      <attribute name="localeIdentifier">
        <value/>

```

```

        </attribute>
        <attribute name="name">

<value>CIIntakeProcess.ApplicationConfiguration.AT19001.RightsAndRespon
value>
        </attribute>
        <attribute name="contentType">
        <value>text/plain</value>
        </attribute>
        <attribute name="contentDisposition">
        <value>inline</value>
        </attribute>
        <attribute name="content">
        <value>./CommonIntake/data/initial/blob/
RightsAndResponsibilitiesText.properties</value>
        </attribute>
        <attribute name="internal">
        <value>0</value>
        </attribute>
        <attribute name="lastWritten">
        <value>SYSTIME</value>
        </attribute>
        <attribute name="versionNo">
        <value>1</value>
        </attribute>
        <attribute name="category">
        <value>RS_PROP</value>
        </attribute>
</row>
<row>
        <attribute name="resourceID">
        <value>19443</value>
        </attribute>
        <attribute name="localeIdentifier">
        <value/>
        </attribute>
        <attribute name="name">

<value>CIIntakeProcess.ApplicationConfiguration.AT19001.AuthorizationIn
value>
        </attribute>
        <attribute name="contentType">
        <value>text/plain</value>
        </attribute>
        <attribute name="contentDisposition">
        <value>inline</value>
        </attribute>
        <attribute name="content">
        <value>./CommonIntake/data/initial/blob/
AuthorizationInformationText.properties</value>
        </attribute>
        <attribute name="internal">
        <value>0</value>
        </attribute>
        <attribute name="lastWritten">
        <value>SYSTIME</value>
        </attribute>
        <attribute name="versionNo">

```

```

        <value>1</value>
      </attribute>
      <attribute name="category">
        <value>RS_PROP</value>
      </attribute>
    </row>
    <row>
      <attribute name="resourceID">
        <value>19444</value>
      </attribute>
      <attribute name="localeIdentifier">
        <value/>
      </attribute>
      <attribute name="name">
        <value>CIIntakeProcess.ApplicationConfiguration.AT19001.DepartmentPolicyText</value>
      </attribute>
      <attribute name="contentType">
        <value>text/plain</value>
      </attribute>
      <attribute name="contentDisposition">
        <value>inline</value>
      </attribute>
      <attribute name="content">
        <value>./CommonIntake/data/initial/blob/
DepartmentPolicyText.properties</value>
      </attribute>
      <attribute name="internal">
        <value>0</value>
      </attribute>
      <attribute name="lastWritten">
        <value>SYSTIME</value>
      </attribute>
      <attribute name="versionNo">
        <value>1</value>
      </attribute>
      <attribute name="category">
        <value>RS_PROP</value>
      </attribute>
    </row>

```

## 2.8) APPRESOURCE.dmx - Entries of various Appresource properties.

Make sure that the files mentioned in the "content" attribute is present in the location specified.

Here it is "CommonIntake/data/initial/blob/" folder

### 3) Following files need to be copied into clob folder:

Note: If the files do not exist then need to create a new files.

#### a) Screening IEG questionnaire script

For ex: Copy FinancialAssistanceApplicationScreening\_V1\_Screening.xml to "CommonIntake\data\initial\clob" folder

#### b) XSD information

For ex: Copy InternalApplication.xsd to "CommonIntake\data\initial\clob" folder

Copy InternalApplicationDomains.xsd to "CommonIntake\data\initial\clob" folder

c) Process Name XML -

For ex: Copy existing CommonIntakeProcess.xml to "CommonIntake\data\initial\clob" folder

d) Rule set XML -

For ex: Copy FinancialAssistanceRuleSet.xml to "CommonIntake\CREOLE\_Rule\_Sets" folder

All the files here have been copied from Intake stream to make Screening configuration.

## Adding urgent alerts to the rule set

To output an urgent alert from the CER rule set, the rule class defined in the screening definition should have an attribute named .

The `alertMessages` attribute has as its type a list of rule classes of type `AlertMessage`. Each `AlertMessage` which is calculated for this list appears as an urgent alert on the **Triage Result** page in the application.

## Recommending programs

To recommend a program from the CER rule set, the rule class that is defined in the screening definition has an attribute named `programs`. This attribute has as its type a list of rule classes that subclass the type `AbstractProgram`. Each `AbstractProgram` is calculated into this list appears as a recommended program on the **screening result** page.

### Specifying whether programs are available internally or externally

Each program that is output from the screening can be available internally or externally. If the program is available internally, then a link to start the application script is displayed. If the program is available externally, then a link to refer the client to the external agency is displayed. Screening results behavior can be defined to specify whether specific programs are available internally or externally as follows:

- Open the `XML` document that represents the intake process definition.
- Locate the `XML` element *Screening* is to be defined.
- For each program that the intake process supports, create an element *ProgramType* as a direct child of the *Screening* element.

Table 5: *ProgramType* Attributes for a Screening

Attribute Name	Type	Purpose
<i>ProgramType</i>	Code Table Entry	Contains an entry from the code table ' <i>ProgramType</i> '. This is a code table that specifies a program type, for example, medical assistance. This attribute is mandatory.
<i>Availability</i>	String	Contains the value ' <i>internal</i> ' if the program is available internally or ' <i>external</i> ' if the program is available from a different agency.

### ***Specifying whether Programs are Available Internally or Externally***

Each program that is output from the screening may be available internally or externally. If the program is available internally, then a link to start the application script is displayed; if the program is available externally, then a link to refer the client to the external agency will be displayed. Screening results behaviour can be defined to specify whether specific programs are available internally or externally. To achieve this:

- Open the XML document which represents the intake process definition.
- Locate the XML element Screening which is to be defined.
- For each program that the intake process will support, create an element ProgramType as a direct child of the Screening element.

Table 6: *ProgramType* Attributes for a Screening

This table describes the attributes that can be set for the *ProgramType* element for a screening.

Attribute Name	Type	Purpose
ProgramType	Code Table Entry	This attribute should contain an entry from the code table 'ProgramType'. This is a code table which specifies a program type, e.g. medical assistance. This attribute is mandatory and must be specified.
Availability	String	This attribute should contain the value 'internal' if the program is available internally or 'external' if the program is available from a different agency.

## **1.4 Configuring Check Eligibility**

### **Introduction**

The check eligibility process allows the user to execute a rule set to determine eligibility for programs applied for on the application. The eligibility rule set outputs a rules decision which

can be displayed on the Eligibility Checks tab after execution. This document outlines the configurations required for this process.

## Configuring an Application Case for Eligibility Checks

There are three configuration options on the application case that drive the check eligibility process.

- **Eligibility Check Rule Set** - the rule set used to check program eligibility. If not specified, the Check Eligibility action item is hidden from the application case tab action menu and the Eligibility Checks tab is not included on the application case
- **Eligibility Check Strategy** - the strategy to be used when checking a client's eligibility for programs associated with an application. This is only applicable when the Eligibility Check Rule Set option is specified. The three options available here are:
  - All
  - Programs Applied for Only
  - User Choice
- **Results Display Page** - this is a dynamic UIM page used to display the eligibility check results. If not specified, no information is displayed on the drop down panel of the check eligibility results page.

The user must configure the eligibility check rule set and results display page. Instructions for doing this are outlined in the following sections.

## Configuring the Eligibility Check Rule Set

The eligibility check rule set must contain a rule class for each program on the application case for which eligibility can be checked. Each rule class must extend the abstract rule class, `AbstractApplicationCaseProgram`, in the `ApplicationCaseCheckEligibilityRulesInterface` rule set. The name of the rule class must correspond to the program type reference of the configured program. In the example below, the rule class is called `ProgramOne`, therefore the program reference must also be called `ProgramOne`.

### Example

```
<Class extends="AbstractApplicationCaseProgram"
  extendsRuleSet="ApplicationCaseCheckEligibilityRulesInterface"
  name="ProgramOne ">
```

Each rule class must implement rules to populate the entitlement and decision rules attributes. If an explanation of the eligibility check needs to be displayed, it's necessary to add display rules to achieve this.

These can be added to the rule class. An annotation of `<Display/>` is required on any rules attributes to be displayed for explanation purposes on the results display page - see the *Inside Cúram Eligibility and Entitlement Using Cúram Express Rules* guide for more information.

## Configuring the Results Display Page

This results display page should invoke the façade method `ApplicationCaseCheckEligibility.viewCheckEligibilityDisplayRules` to retrieve the display rules. The dynamic UIM page should contain the page parameter `appCaseEligibilityResultID` which should be passed into the façade method. The rules are returned from the façade method as XML in an attribute called `displayXML`. This attribute is used on the dynamic UIM page for displaying the data required for explanation purposes. The individual elements to be displayed to the user are retrieved using extended path expressions in the dynamic UIM page.

### Example

If a display attribute called `Income` has been added to our rule set, retrieval of this information would be achieved by adding the following XML to the display rules page:

```
<FIELD
  DOMAIN="CURAM_AMOUNT"
  LABEL="Field.Label.Income">
  <CONNECT>
    <SOURCE
      EXTENDED_PATH="/DecisionDetails/ProgramOne/Income"
      NAME="DISPLAY"
      PROPERTY="displayXML"
    />
  </CONNECT>
</FIELD>
```

The first item in the `EXTENDED_PATH` is always `DecisionDetails`, with the remainder of the path pointing to the attribute in the custom rule class.

## 1.5 Configuring a PCR Rule Set

### Introduction

This chapter provides an overview of the PCR rule set structure and details how a customer can create a PCR rule set. PCR rule sets are used to calculate a result for the priority, complexity, and risk rating for a case scenario. Each of the components which make up a PCR assessment is represented as an attribute in the PCR rule set. A rule can have an associated weighting which is added to the overall PCR calculation if it succeeds. The rules then determine the overall rating and classification of the case.

### Configuring a PCR Rule Set

Each PCR Rule Set must contain a rule class which inherits from the `AbstractPCR` class. This rule class is the class which produces the PCR results to be displayed to the worker.

To create a PCR rule class, first create the rule class using the CER editor, naming the rule class appropriately.

The usage of the PCRRuleSet rule class guarantees that the required attributes are available during rules execution. For more information on setting up rule sets, see the *Cúram Express Rules Cookbook*.

A PCR rule set must inherit from the PCRRuleSet and provide an implementation for each of the six abstract attribute within the defined rule set. The description attribute is inherited from the root rule class and each solution must also provide its own implementation of this attribute.

## Mandatory Rule Attributes

Table 7: Mandatory Rule Attributes for PCR Rule Sets

This table describes mandatory rule attributes to be used for PCR rule sets

Rule Attribute	Type	Purpose
caseID	Number	Specified case identifier attribute for which the PCR rules execution relates to.
description	String	This attributes represents the text defining the property description. The value that this attribute contains is a reference to one or more properties in a property file containing the actual text.
priorityRate	Number	This attribute is a calculated attribute representing the relative ranking of the case against a baseline to determine a timeline for response.
priorityReason	String	This attribute represents the text defining the property priority reason. The value that this attribute contains is a reference to one or more properties in a property file containing the actual text.
complexityRate	Number	This attribute is a calculated attribute representing the ranking of a case against a baseline to determine the resource(s) required for a response.
complexityReason	String	This attributes represents the text defining the property complexity reason. The value that this attribute contains is a reference to one or more properties in a property file containing the actual text.
riskRate	Number	This attribute is a calculated attribute representing the relative ranking of a case against a baseline to determine its potential impact to the agency.

Rule Attribute	Type	Purpose
riskReason	String	This attributes represents the text defining the property risk reason. The value that this attribute contains is a reference to one or more properties in a property file containing the actual text.

## Specifying Rule Set Properties Text

The rule set properties text is specified by creating an entry in a localized property file as follows:

- Create a property file, for example, PCRSample.properties.
- Add each entry to the property file that will be referenced by the Rule Class attributes. The value of each of these entries is the localized text to be displayed in the application. The following example outlines an example property entry in a PCRSample.properties file and how the property is referenced by a rule set attribute:

```
# This Properties file contains resource
strings for the Sample PCR Rule set.
PCRSample.description=PCRSample
PCRSample.samplePriorityReason=Sample Priority Reason

<Attribute name="description">
  <type>
    <javaclass name="curam.creole.value.Message"/>
  </type>
  <derivation>
    <ResourceMessage
      key="PCRSample.description"
      resourceBundle="curam.pcrsample.rules.PCRSample"
    >
    </ResourceMessage>
  </derivation>
</Attribute>
```

- Add the Properties file entry to the Resource Store by updating the 'Dynamic UIM' section of the Administration Application. In the above example, this entails adding a PCRSample.properties entry in the Dynamic UIM section of the administration application, along with a corresponding page ID, a resource store category, and a properties file.

## 1.6 Configuring Authorization Rule Sets

### Introduction

This chapter covers the rule sets used during authorization and the necessary configurations required by a custom solution.

### Intake Rule Sets

There are two rule sets shipped by default with Intake:

- `ApplicationAuthorisationInterfaceRuleSet`
- `ClientSelectionInterfaceRuleSet`

These provide flexibility to customers with regard to the strategies for program authorization, namely the determination of the programs to be authorized and the clients to be added to a product delivery as part of program authorization.

## Determining the Programs to be Authorized

When authorizing at the application case level, the programs to be considered must be determined using rules. This is done via the `ApplicationAuthorisationInterfaceRuleSet` rule set.

## Writing the Authorize Application Rule Class

The rule class for governing application authorization must extend from the abstract class `ApplicationAuthorisationInterfaceRuleSet.AbstractApplicationCase`. Here is a description of the attribute(s) inherited from `AbstractApplicationCase`:

*Table 8: Abstract Attribute(s) To Be Implemented*

Rule Attribute Name	Data Type	Description
programs	List of Program	The programs to be authorized on the application.

Program is an instance of the `ApplicationAuthorisationInterfaceRuleSet.Program` class. As it's optional for a product delivery to be created on authorization, `ApplicationAuthorisationInterfaceRuleSet.Program.primaryClient` is defaulted to null and

`ApplicationAuthorisationInterfaceRuleSet.Program.additionalClients` is defaulted to an empty list.

A basic implementation might be the retrieval of all programs in a state of 'Pending' that are associated with the application case.

## Determining the Clients to be Added to the Product Delivery

One of the configurations on a program is Client Selection Strategy. This can be one of the following:

- All
- User Selection
- Rules

The Rules strategy is governed by the `ClientSelectionInterfaceRuleSet` rule set.

## Writing the Client Selection Rule Class

The rule class for governing client selection must extend from the abstract class `ClientSelectionInterfaceRuleSet.AbstractClients`. Here is a description of the attribute(s) inherited from `AbstractClients`:

*Table 9: Abstract Attribute(s) To Be Implemented*

Rule Attribute Name	Data Type	Description
<code>primaryClient</code>	<code>Client</code>	The primary client for the product delivery being created as a result of authorization.

`Client` is an instance of `ClientSelectionInterfaceRuleSet.Client`.

## 1.7 Intake Process XML Definition

This appendix provides a high level overview of the XML definition for an intake process.

### Intake Process XML Definition

```
<IntakeProcess>
  <GlobalConfiguration>
  </GlobalConfiguration>
  <IndividualConfiguration>
    <Triage DataStore="Triage" RuleSet="SampleTriageRuleSet"
      RuleSetClass="Triage" ScriptName="Triage" ScriptType="Screening"
      ScriptVersion="V1"/>
    <Screening DataStore="Screening" RuleSet="SampleScreeningRuleSet"
      RuleSetClass="ScreeningResult" ScriptName="SampleScreening"
      ScriptVersion="V1" type="SC12345">
      <DisplayStatus status="SS12345"/>
      <DisplayStatus status="SS67890"/>
    </Screening>
  </IndividualConfiguration>
</IntakeProcess>
```

## 1.8 Intake Environment Variables

### Application Properties

This appendix describes application properties for Intake. These may be administered through the Cúram system administration application - see the Cúram System Configuration Guide for more information.

Table 10: Intake Environment Variables

This table contains Intake environment variables.

Property Name	Description	Default
curam.intake.map.default.zoom.level	This property is used to define the initial zoom level of the Google Maps display on the Service Provider screen. Zoom levels between 0 (the lowest zoom level, in which the entire world can be seen on one map) to 21+ (down to individual buildings) are possible.	11
curam.intake.map.default.center.latitude	This property is used to define the default latitude of the center of the Google Maps display on the Service Provider screen.	-89.40570831298828



# Notices

---

Permissions for the use of these publications are granted subject to the following terms and conditions.

## **Applicability**

These terms and conditions are in addition to any terms of use for the Merative website.

## **Personal use**

You may reproduce these publications for your personal, noncommercial use provided that all proprietary notices are preserved. You may not distribute, display or make derivative work of these publications, or any portion thereof, without the express consent of Merative

## **Commercial use**

You may reproduce, distribute and display these publications solely within your enterprise provided that all proprietary notices are preserved. You may not make derivative works of these publications, or reproduce, distribute or display these publications or any portion thereof outside your enterprise, without the express consent of Merative.

## **Rights**

Except as expressly granted in this permission, no other permissions, licenses or rights are granted, either express or implied, to the publications or any information, data, software or other intellectual property contained therein.

Merative reserves the right to withdraw the permissions granted herein whenever, in its discretion, the use of the publications is detrimental to its interest or, as determined by Merative, the above instructions are not being properly followed.

You may not download, export or re-export this information except in full compliance with all applicable laws and regulations, including all United States export laws and regulations.

MERATIVE MAKES NO GUARANTEE ABOUT THE CONTENT OF THESE PUBLICATIONS. THE PUBLICATIONS ARE PROVIDED "AS-IS" AND WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, NON-INFRINGEMENT, AND FITNESS FOR A PARTICULAR PURPOSE.

Merative or its licensors may have patents or pending patent applications covering subject matter described in this document. The furnishing of this documentation does not grant you any license to these patents.

Information concerning non-Merative products was obtained from the suppliers of those products, their published announcements or other publicly available sources. Merative has not tested those products and cannot confirm the accuracy of performance, compatibility or any other claims related to non-Merative products. Questions on the capabilities of non-Merative products should be addressed to the suppliers of those products.

Any references in this information to non-Merative websites are provided for convenience only and do not in any manner serve as an endorsement of those websites. The materials at those

websites are not part of the materials for this Merative product and use of those websites is at your own risk.

This information contains examples of data and reports used in daily business operations. To illustrate them as completely as possible, the examples include the names of individuals, companies, brands, and products. All of these names are fictitious and any similarity to actual people or business enterprises is entirely coincidental.

The licensed program described in this document and all licensed material available for it are provided by Merative under terms of the Merative Client Agreement.

#### **COPYRIGHT LICENSE:**

This information contains sample application programs in source language, which illustrate programming techniques on various operating platforms. You may copy, modify, and distribute these sample programs in any form without payment to Merative, for the purposes of developing, using, marketing or distributing application programs conforming to the application programming interface for the operating platform for which the sample programs are written. These examples have not been thoroughly tested under all conditions. Merative, therefore, cannot guarantee or imply reliability, serviceability, or function of these programs. The sample programs are provided "AS IS", without warranty of any kind. Merative shall not be liable for any damages arising out of your use of the sample programs.

## ***Privacy policy***

---

The Merative privacy policy is available at <https://www.merative.com/privacy>.

## ***Trademarks***

---

Merative™ and the Merative™ logo are trademarks of Merative US L.P. in the United States and other countries.

IBM®, the IBM® logo, and ibm.com® are trademarks or registered trademarks of International Business Machines Corp., registered in many jurisdictions worldwide.

Adobe™, the Adobe™ logo, PostScript™, and the PostScript™ logo are either registered trademarks or trademarks of Adobe™ Systems Incorporated in the United States, and/or other countries.

Oracle and Java are registered trademarks of Oracle and/or its affiliates.

The registered trademark Linux® is used pursuant to a sublicense from the Linux Foundation, the exclusive licensee of Linus Torvalds, owner of the mark on a worldwide basis.

Microsoft™, Windows™, and the Windows™ logo are trademarks of Microsoft™ Corporation in the United States, other countries, or both.

UNIX™ is a registered trademark of The Open Group in the United States and other countries.

Other company, product, and service names may be trademarks or service marks of others.